

# 1605 BUTANE ADAPTER



## 2 good reasons why you need a GASLOW

### Ever Run Out Of Gas – Yes!

Have you noticed it always seems to be at the worst time, its either raining, in the middle of the night – or BOTH.

That's Annoying !

The GASLOW removes these problems

### Leak Detection

You can carry out a quick and very effective test that checks your complete gas system for leaks.

### Thought You Could Smell Gas – Yes!

A potentially dangerous situation and you have no quick and reliable way of checking that everything is safe.

That's Worrying !

### Low Level Indicator

Provides you with visual warning of low gas levels so there will be no more surprises.

Be Sure.....Be Safe.....Fit a GASLOW

## OPERATING INSTRUCTIONS. To be kept by user.

### Connecting to your Gas System

- Ensure the gas supply is turned OFF at the cylinder.
- Check your Gaslow making sure the connections are clean and free from damage
- Check the rubber washers then connect the Gaslow to the gas cylinder tightly with a spanner, remembering this is a left hand thread.

IMPORTANT: Once the Gaslow has been fitted to your regulator, or hose leave permanently connected. To change gas cylinders, disconnect



Should there be a leak it is important to identify the source before using your gas system. Use a recommended leak detector or a soapy water solution – NEVER USE A NAKED FLAME. Testing for leaks should start at the gas cylinder working back to your appliances.

IMPORTANT: The RED sector will appear over a longer period of time because your system will not maintain gas pressure indefinitely.

### Operating as a Low Level Indicator

- The Gaslow gives you warning of low gas levels ONLY when gas has been consumed for at least 10 minutes. ALWAYS ENSURE YOU ARE BURNING GAS OR HAVE JUST FINISHED WHEN READING THE GASLOW.

For best results we recommend a high consumption appliance such as a cooker or heater, NOT A FRIDGE OR PILOT BURNER as they consume very little gas and will give inaccurate readings and insufficient warning of gas exhaustion.

- On a low consumption appliance the gauge will indicate longer cylinder life. If a high consumption appliance were then used, the gauge would adjust to show a shorter cylinder life.

IMPORTANT: The Gaslow allows for ambient temperatures with sectors on the dial face marked 'hot day', 'cool day' and 'cold day'. Read the needle on the outer band when it's cold and the inner when it's hot.


During cold weather, the GASLOW will register in the red when there is still liquid in the cylinder. This occurs as Butane gas will not operate when temperatures fall close to freezing.

### Operating as a Leak Detector

Leak testing is quick and easy and we recommend this procedure is performed every time the gas is turned on at the cylinder.

- Ensure ALL gas appliances are turned OFF.
- Turn ON the gas and pressurise the system.
- The gauge will show GREEN.
- Turn OFF the gas supply. The Gaslow will now monitor the gas pressure in your system between the gas cylinder and the appliances.

ANY LEAKS WILL BE INDICATED BY THE RED SECTOR APPEARING WITHIN 5 MINUTES.



### Optional adapters (for Butane cylinders)

For 7 & 15Kg cylinders, a 21mm Clip-on adapter is required. A special adapter is needed for Camping Gas cylinders.



## BUTANE Gauge

- Warns of low gas supply
- Detects dangerous gas leaks
- Fits 4.5kg gas cylinders
- Fits butane high pressure hoses
- Simple to install

**2004 EN1949**  
This Gaslow will fit NEW 30mbar caravan regulators

Prod.Code 01-1605



### General Safety and Operating Conditions

- Storage area, must be well ventilated.
- Use no naked flames, cigarettes, matches etc in the vicinity when connecting disconnecting or when operating the gas supply.
- The gas cylinder must ALWAYS be used in the upright position.
- When used outdoors the Gaslow must be suitably protected from the elements.
- Should there be any queries please contact your local dealer or Gaslow direct.

Gaslow International Limited  
Unit 1, Weldon Road  
Loughborough  
Leicestershire LE11 5RA  
Tel 0845 4000 600  
Info@gaslow.co.uk  
www.gaslow.co.uk



Made in the EEC  
UK Patent No: 2301895  
Euro Patent No: 0754294

